


OFFICE OF THE MARION COUNTY SURVEYOR
SECTION RECORD CORNER
SECTION 13 TOWNSHIP 17 RANGE 2
DATE: --9-26-99--- 2-21-04
PARTY CHIEF: Wilcoxen--- Kiste
CREW: _____
TYPE OF MARKER: Harrison
METHOD OF ESTABLISHMENT: County: 8-9-94

IN. S.P.C. E ZONE, NAD 83
NAME: 17021301
N: 519370.1180(m)
E: 49290.4820(m)



Original post set 1821 by Laughline with witnesses: 12" beech N 66 E 25 links, 12" elm S 56 W 20 links per Marion County Atlas pg. 4. Hosbrook 8-7-1851 called rock set with stump per Pike Township Legal Survey Book pg. 39. Burres 1-23-64 called the same. McLand 10-10-69 called out nothing at surface. Wilcoxen 11-9-76 called a railroad spike. Cleveland 6-5-85 called railroad spike found. Excavated by Wilcoxen 8-9-94 and capped rebar was found 3' down. Another railroad spike was found 7' down. Harrison set. Re-tied 9-26-99 by Wilcoxen.

HC721301

| REF. | DISTANCE | DESCRIPTION |
|------|----------|--|
| 1. | 86.19' | Cut 'x' Westerly bolt of aluminum pole base |
| 2. | 113.28' | PK nail NW PwP#199-207 30'up |
| 3. | 128.91' | PK nail S PwP#199-208 6'up |
| 4. | 91.70' | Top nut of fire hydrant |
| 5. | 68.70' | Cut 'x' Westerly bolt of aluminum pole base |
| 6. | 67.92' | Cut 'x' Easterly bolt of aluminum pole base |
| 7. | 83.42' | Cut 'x' Southerly bolt of aluminum pole base |
| 8. | 54.47' | Cut 'x' in S-end of median |
| | | |
| | | |